

Emotion Transfer for Hand Animation

Ana-Sabina Irimia
Northumbria University

Jacky C. P. Chan
Caritas Institute of Higher Education

Kamlesh Mistry
Northumbria University

Wei Wei
Xi'an University of Technology

Edmond S. L. Ho*
Northumbria University

ABSTRACT

We propose a new data-driven framework for synthesizing hand motion at different emotion levels. Specifically, we first capture high-quality hand motion using VR gloves. The hand motion data is then annotated with the emotion type and a latent space is constructed from the motions to facilitate the motion synthesis process. By interpolating the latent representation of the hand motion, new hand animation with different levels of emotion strength can be generated. Experimental results show that our framework can produce smooth and consistent hand motions at an interactive rate.

CCS CONCEPTS

• **Computing methodologies** → **Animation**; *Machine learning*.

KEYWORDS

hand animation, emotion, motion capture, style transfer

ACM Reference Format:

Ana-Sabina Irimia, Jacky C. P. Chan, Kamlesh Mistry, Wei Wei, and Edmond S. L. Ho. 2019. Emotion Transfer for Hand Animation. In *MIG '19: ACM SIGGRAPH conference on Motion, Interaction and Games, Oct 28–30, 2019, Newcastle upon Tyne, UK*. ACM, New York, NY, USA, 2 pages. <https://doi.org/10.1145/1122445.1122456>

1 INTRODUCTION

This paper introduces a new method of style transfer for hand animation. The first objective of our method is to create new motions by adding synthesized styles to a base motion. Our method first extracts the style from motions and applies it to a base motion to create new animations for the character. The second objective of the project is to create motions for the character that present four emotions: anger, sadness, fear, and joy. The character can express those emotions only by its hand movement, as some characters may not have a face or voice to express their emotions. Using only their fingers and palm, making it a challenging task for an existing method to express the emotions.

Liu et al. proposed an interactive physics-based motion synthesis technique for manipulating a 3D hand model [6]. The interactive

*Corresponding author. email: e.ho@northumbria.ac.uk

Permission to make digital or hard copies of all or part of this work for personal or classroom use is granted without fee provided that copies are not made or distributed for profit or commercial advantage and that copies bear this notice and the full citation on the first page. Copyrights for components of this work owned by others than ACM must be honored. Abstracting with credit is permitted. To copy otherwise, or republish, to post on servers or to redistribute to lists, requires prior specific permission and/or a fee. Request permissions from [permissions@acm.org](https://permissions.acm.org).

MIG '19, Oct 28–30, 2019, Newcastle upon Tyne, UK

© 2019 Association for Computing Machinery.

ACM ISBN 978-1-4503-9999-9/18/06...\$15.00

<https://doi.org/10.1145/1122445.1122456>

physics-based simulation algorithm is capable of creating seemingly mundane hand movements that are hard to achieve with keyframe animation or motion capture. An optimization-based approach to hand manipulation of grasping pose is introduced by Liu et al. [7]. The process of animating the hand is an automatic method that starts by inserting the initial input, the grasping pose, and the partial trajectory of the object, thus resulting in a physically plausible hand animation. Ye et al. presented a randomized sampling algorithm that can synthesize detailed and physically plausible hand manipulation given input full-body human motion and interacting object [9]. Yunfei Bai and C. Karen Liu proposed a solution to the problem of manipulating the orientation of a polygonal object using both palm and fingers of a robotic hand [1]. The aforementioned methods can acquire hand motion for performing a specific task in only a single style or a random style. In this paper, we would like to generate hand motion with styles specified by user.

The contributions in this work can be summarized as follows:

- We captured and annotated a new hand motion dataset with 7 motion types in 5 different emotions.
- We proposed an efficient hand motion synthesis framework which can be used for synthesizing new hand motion with different emotion strength levels at an interactive rate.

2 METHODOLOGY

2.1 Motion Capture

To the best of our knowledge, there is no publicly available hand motion dataset with a wide range of hand motions as well as different emotion stats and styles. We decided to use the Senso VR glove (<https://senso.me/>) to capture hand motion in this research. Each frame in the hand motion is represented by a vector P_j

$$P_j = [p_{0,x}, p_{0,y}, p_{0,z}, \dots, p_{n-1,x}, p_{n-1,y}, p_{n-1,z}] \quad (1)$$

where j is the frame index, n is the total number of joints and $n = 23$ in the hand model we used, and p is the joint angle of the corresponding joint and rotation axis, respectively. We removed the hand translations in this research to avoid the artifacts caused by the incorrect hand translations tracked by the gloves. We captured 7 different types of hand motion, including *Crawling*, *Gripping*, *Pat*, *Impatient*, *Hand on Mouse*, *Pointing and Pushing*, and 5 different emotions are associated with each motion type (i.e., *neutral*, *angry*, *happy*, *sad*, and *scary*). In total, we captured 35 motion sequences.

2.2 Standardizing Hand Motions

Standardizing raw data is an important step before we statistically model the hand motion for the motion synthesis tasks. In particular, motion sequences are usually having a different duration. To facilitate the data standardization process, the subject performed each motion type in exactly 2 cycles. In this work, we take a simple

